



PHONE: (864) 288-4255 FAX: (864) 752-1650

Email us: machinetools@mindspring.com

Visit Our Website at www.machinetoolsinc.com

Dear Customer,

We are pleased to offer for your consideration:

**ONE (1) NEW U.S. INDUSTRIAL 200 TON X 13 HYDRAULIC PRESS BRAKE
WITH FRONT OPERATED POWER BACKGAUGE AND POWER RAM ADJUST**

Model Number: USHB200-13HM

STANDARD EQUIPMENT: (All of the following comes with the machine)

- Power Front Operated Back Gauge, motorized with fine adjustment handwheel
- Power Ram Depth Control, motorized with fine adjustment handwheel
- Digital Displays for backgauge position and ram position
- All Steel Construction
- Sick 4000 Light Curtain
- Ram accepts standard American Tang tooling, 1/2" x 5/8"
- Space between Ram Tool Clamps allows for deep box bending
- Bed has slot for standard American Tang tooling
- Bed also has capture clamps for tooling without tang
- Free Gooseneck Punch and multi-opening Die for up to 90° forming in 10 gauge mild steel
- (see note on page 2)

SPECIFICATIONS:

• Working Pressure:	200 Tons	• Pressing Speed:	Dependent on Tool Load
• Length of Working Table:	157.4"	• Hydraulic Oil Capacity:	97 Gal.
• Distance Between Housings:	124"	• Motor Horsepower:	20 HP
• Throat Depth:	12.5"	• Net Weight:	28,660 lbs.
• Stroke Adjustment of Ram:	2.75"	• Length:	179"
• Ram Travel:	7.0"	• Width:	64"
• Open Height:	17.5"	• Height:	101"
• Rapid Ram Travel Speed:	2.4"/sec.		
• Rapid Ram Retreat Speed:	2.0"/sec.		
• Backgauge Travel:	24"		

*** Continued on Page 2 ***

*specifications are subject to change without notice

